

AR30




SPECIFICATIONS


- Best Operating Frequency:** 30 kHz, $\pm 4\%$
- Minimum Transmit Sensitivity at Best Transmit Frequency:** 105 dB, 1 $\mu\text{Pa/V}$ at 1 m
- Minimum Receive Sensitivity at Best Receive Frequency:** -155 dB re 1V/ μPa
- Minimum Parallel Resistance:** 700 Ω , $\pm 30\%$
- Minimum and Maximum Sensing Range*:** 60 cm to 30 m
- Typical Sensing Range:** 80 cm to 25 m
- Free (1 kHz) Capacitance:** 5,700 pF, $\pm 1,000$ pF
- Beamwidth (@ -3 dB Full Angle):** 12°, $\pm 2^\circ$
- Maximum Driving Voltage (2% Duty Cycle Tone Burst):** 2,200 V_{pp}
- Operating Temperature:** -40°C to 90°C
- Weight:** 800 g
- Housing Material:** Glass filled polyester
- Acoustic Window:** Glass reinforced epoxy

*Pulse-Echo Mode. Minimum and maximum ranges are best case scenarios. Actual range may vary, depending on drive circuitry and signal processing.

Directivity Pattern



Transmit & Receive Voltage Response



Impedance Magnitude & Phase





Figure of Merit (Sum of TVR & RVR)



30 kHz

AIRDUCER® Ultrasonic Transducer

Applications

- Level measurement
- Proximity
- Obstacle avoidance
- Traffic control


Features

- Rugged sealed construction
- Housing design will accommodate transceiver and signal processing electronics
- Mounting cap available in BSP, NPT, or M32 threads
- Standard internal shielding

Options

- Cylinder housing available with mounting cap kit
- Complete assembly available with standard cable lengths
- 10 K Ω thermistors are optional for temperature compensation
- Available in PVDF housing for use in chemically aggressive environments
- FM approved

Dimensions



©Airmar Technology Corporation

AR30_r1 02/16/11

As Airmar constantly improves its products, all specifications are subject to change without notice. All specifications typical at 22°C. Factory Mutual approved models suitable for: Class I, Division 1, Hazardous Locations. AIRDUCER® is a registered trademark of Airmar Technology Corporation. Other company or product names mentioned in this document may be trademarks or registered trademarks of their respective companies, which are not affiliated with Airmar.



www.airmar.com